



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax : (86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ LCD Digital Advertising Player

Model No:PDP-L420A



LTD.

Model No: PDP-L420A

Metal Frame, Horizontal

42inches excellent PDP Panel with high resolution, wide visual angle and rich color.

The card interface of CF, use CF card to store and broadcast the program.

Support JPG, MPEG1, MPEG2, MP3, MPEG4 (DIVX, XVID) format.

Remote control unit.

Can be used in subway station, hotel, lift, boardroom, classroom, shop, supermarket and public areas or aboard Various forms of transportation, like taxi ,train etc.

Technical parameter

·Working temperature: 5℃~60℃

·Size of the machine: 1026 x627x76 mm

·Active Area: 933.0 x 533.5 mm (H x V) ·

Pixel pitch: 1.095(H) x 1.110(V) mm

·Number of colors: 16.7 M

·Brightness: 650cd/m²

·Contrast ratio: 3000:1

·Viewing Angle: U80 /D80 /L80/R 80

·Input voltage: Exchange220V (50HZ-60HZ)

·the power is managed: Accord with the power of VESA DPMS

·Standard power: 310W

·Stereo rated power: 2 x 5W

Outer packing

Carton size: 1165x155x710 mm

QTY: 1 PCS/CTN

© 1997-2006, S.G. INTERNATIONAL GROUP H.K. LTD. All rights reserved.

Buji Town, Shenzhen 518123, China

Tel: +86-755-25387626 , 84701880 , Fax: +86-755-84701680

Sales email: sgled@vip.163.com

ISO 9001:2000



Cert. #801532



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax : (86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ LCD Digital Advertising Player

Model No:PDP-L420B



Model No: PDP-L420B

Model No: PDP-L420B

Metal Frame, Vertical

42Inches excellent PDP Panel with high resolution, wide visual angle and rich color.

The card interface of CF, use CF card to store and broadcast the program.

Support JPG, MPEG1, MPEG2, MP3, MPEG4 (DIVX, XVID) format.

Remote control unit.

Can be used in subway station, hotel, lift, boardroom, classroom, shop, supermarket and public areas or aboard Various forms of transportation, like taxi ,train etc.

Technical parameter

·Working temperature: 5°C ~60°C

·Size of the machine: 1026 x627x76 mm

·Active Area: 933.0 x 533.5 mm (H x V)

·Pixel pitch: 1.095(H) x 1.110(V) mm

·Number of colors: 16.7 M

·Brightness: 650cd/m²

·Contrast ratio: 3000:1

·Viewing Angle: U80 /D80 /L80/R 80

·Input voltage: Exchange220V (50HZ-60HZ)

·The power is managed: Accord with the power of VESA DPMS

·Standard power: 310W

·Stereo rated power: 2 x 5W

Outer packing

Carton size: 1165x155x710 mm

QTY: 1 PCS/CTN

© 1997-2006, S.G. INTERNATIONAL GROUP H.K. LTD. All rights reserved.

Buji Town, Shenzhen 518123, China

Tel: +86-755-25387626 , 84701880 , Fax: +86-755-84701680

Sales email: sgled@vip.163.com

ISO 9001:2000



Cert. #801532



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax : (86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ LCD Digital Advertising Player

Model No:LCD-L420L



Model No: LCD-L420L

Model No: LCD-L420L

Metal Frame, Vertical

42inches excellent PDP Panel with high resolution, wide visual angle and rich color.

The card interface of CF, use CF card to store and broadcast the program.

Support JPG, MPEG1, MPEG2, MP3, MPEG4 (DIVX, XVID) format.

Remote control unit.

Can be used in subway station, hotel, lift, boardroom, classroom, shop, supermarket and public areas or aboard Various forms of transportation, like taxi ,train etc.

Technical parameter

- Working temperature: 5°C~60°C
- Aspect Ratio: 16:9
- Color : 16,77M Colors (256 levels)
- Brightness: 1000cd/m2
- Contrast Ratio: 1000:1
- work temperature: 0-40°C
- Power Input: AC90-264V 50/60Hz
- Net Weight : 36 KG
- Dimension of products(L x W x H): 900X 400 X 1875mm

© 1997-2006, S.G. INTERNATIONAL GROUP H.K. LTD. All rights reserved.

Buji Town, Shenzhen 518123, China

Tel: +86-755-25387626 , 84701880 , Fax: +86-755-84701680

Sales email: sgled@vip.163.com

ISO 9001:2000



Cert. #801532



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ LCD Digital Advertising Player

Model No:LCD-L42A



Model No: LCD-L42A

Resolution: 1366*768

Pixel Pitch: 0.5025*0.1625

View Angle: 178/178

Contrast Ratio: 1600:1

Brightness: 600 (cd/m2)

Total Response Time: 8ms

Max Consumption: 45W

TV Features

PC VGA: analog, 0.7Vp-p, with TTL H/V sync

Video: 1.0Vp-p, embedded sync

Audio: 0.5Vrms

Headphone out: 100mW (type).

Input / Output Port:

VGA. AV. TV. S-Video, YPbPr, YCbCr. Scar. Teletext. DVI

TV format:

1, PAL DK/I/B.G, or NTSC M/N, or SECAM (optional)

2, Video input format: PAL, NTSC, and SECAN

3, Power Supply: DC: 12 V3.0-4.5A (according on different model)

4, 256 TV channels

5, OSD LANGUAGES: English, Russian, Spanish, Italian, Protuguese, Korea, Japanese, French, Germany, Shinese

6, PIP/POP/PBP

Main Features of Advertising Players.

1, Support video Ads files such as MPEG-1, MPEG-4, VCD, DVD,

2, Support common audio files as MP3, AWA, etc.

3, Support the photo files formats as JPEG, BMP, GIF, meet the photo file formats, of common digital equipment.

4, Play in memory cards, Such as CF, SD.

5, loudspeaker built in, broadcast in, the video Ads in a circle

6, View the picture in a various modes, one by one, by slide music, meanwhile can restate the photo up to down, or left-to-right.

7, Familiar with Windows manage resource support the online files

8, displaying the image clarified, supporting PC, AV, S-Video and TV interface



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ LCD Digital Advertising Player

Model No:LCD-L42B



Model No: LCD-L42B

Resolution: 1366*768

Pixel Pitch: 0.5025*0.1625

View Angle: 178/178

Contrast Ratio: 1600:1

Brightness: 600 (cd/m2)

Total Response Time: 8ms

Max Consumption: 45W

TV Features

PC VGA: analog, 0.7Vp-p, with TTL H/V sync

Video: 1.0Vp-p, embedded sync

Audio: 0.5Vrms

Headphone out: 100mW (type).

Input / Output Port:

VGA. AV. TV. S-Video, YPbPr, YCbCr. Scar. Teletext. DVI

TV format:

1, PAL DK/I/B.G, or NTSC M/N, or SECAM (optional)

2, Video input format: PAL, NTSC, and SECAN

3, Power Supply: DC: 12 V3.0-4.5A (according on different model)

4, 256 TV channels

5, OSD LANGUAGES: English, Russian, Spanish, Italian, Protuguese, Korea, Japanese, French, Germany, Shinese

6, PIP/POP/PBP

Main Features of Advertising Players.

1, Support video Ads files such as MPEG-1, MPEG-4, VCD, DVD,

2, Support common audio files as MP3, AWA, etc.

3, Support the photo files formats as JPEG, BMP, GIF, meet the photo file formats, of common digital equipment.

4, Play in memory cards, Such as CF, SD.

5, loudspeaker built in, broadcast in, the video Ads in a circle

6, View the picture in a various modes, one by one, by slide music, meanwhile can restate the photo up to down, or left-to-right.

7, Familiar with Windows manage resource support the online files

8, displaying the image clarified, supporting PC, AV, S-Video and TV interface