



# S.G. INTERNATIONAL GROUP H.K. LIMITED

## SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax : (86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: [sgled@vip.163.com](mailto:sgled@vip.163.com)

MSN: [sgled@hotmail.com](mailto:sgled@hotmail.com)

Yahoo Messenger: [sgled\\_usa@yahoo.com](mailto:sgled_usa@yahoo.com)

### ➤ GPRS Wireless Network Adapter



### GPRS Wireless Network Adapter

#### Introduce Product

Integrating high-speed wireless network with powerful PC system, GPRS Wireless Network Adapter is newly unveiled product of t f net. It offers high quality and valuable data service for customers under every circumstance, such as email transfer, electronic business, mobile office and point-to-point data exchange. With the highlight of real-time data transfer worldwide, it combines mobile communication with Internet so as to make you surfing on Internet absolutely freely.

#### System Functions:

High-speed

Up to 115kbs high speed (scalable)

Auto-roaming

Internet surfing any time and any place

Multi-payment

Variable ways of payment available without additional charge for auto-roaming homeland

Easy to apply

Only one call will make everything OK.

#### System Features:

USB interface without the expense of an external boost supply.

Voice transmission available

Message and facsimile transmission supported

SIM card compatible (applied with e-card)

Operating system optional (Windows95/98/me/2000/NT 4.0/XP)

#### Power Supply

1. GSM 900MHz Band

Forwarding Frequency: 880-915MHz

Receiving Frequency: 925-960MHz

Output Power: 2W (+33dBm)

2. DCS1800MHz Band

Forwarding Frequency: 1710-1785MHz

Receiving Frequency: 1805-1880MHz

Output Power: 1W (+30dBm)

3. Channel Difference: 200 KHz

4. Frequency Reliability: 0.1ppm

5. Operating Temperature:-20°C~ 60°C

6. Storage Temperature:-30°C ~ 85°C

7. Humidity: 95%

8. Vibration (non-operating status):20g

9. Operating Input: 5V (USB port available)

10. Standby Current: 10Ma