



# S.G. INTERNATIONAL GROUP H.K. LIMITED

## SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax : (86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: [sgled@vip.163.com](mailto:sgled@vip.163.com)

MSN: [sgled@hotmail.com](mailto:sgled@hotmail.com)

Yahoo Messenger: [sgled\\_usa@yahoo.com](mailto:sgled_usa@yahoo.com)

### ➤ Hand-Free VoIP Internet Phone HP10



#### Overview

VoIP HP10 is your ultimate source to free you from all the outdated gadgets of headsets and the microphone which were used earlier for the process of internet voice chat on VoIP.

Just a click and you have a freedom from the length limitation of wires.

Using an echo cancellation technology provides you a high quality internet phoning environment. The simple operating buttons makes you feel much more comfortable to use and with the technology it not only allows you for a free mobility but as well to be used in various multimedia demands, especially in the times of conference meeting where everybody is heard loud and clear.

Easy to use and install. The technicality is so that you don't have to worry much about the installation. Just plug in the speaker and get started. Since the speaker is fully compliant with USB 1.0/2.0 standards and top it out our user-friendly driver installation you are ready for unlimited VoIP chat.

#### Features

Hands Free Speaker Phone for PC VoIP.

Superior Echo Cancellation

Noise Suppression & Far Field Pickup

Full Duplex Voice Communication.

Plug & Play (USB) for NB/DT PC

Comply with PC VoIP free application software such as Yahoo, MSN, Skype and QQ.

Full Spectrum Stereo Music (Headset Jack).

No AC/DC Adapter (Powered by USB).

Privacy Mode (Headset Jack).

Portable (Small and Light).

#### Specifications

Acoustic Echo Cancellation: 45 - 55 dB

Noise Suppression: 13 - 15 dB

Speaker Volume: 95 dB @ 30cm

Voice Pick Up Distance: up to 3 m

Operating Temperature : 0° ~ 40°

Humidity : 10%~90% non-condensing

Conformance : FCC / CE