



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display

	<p>SG12.1-inch LCD Touch Monitor</p> <ol style="list-style-type: none"> 1.Flat chassis design: using on the desk, the display does not swag when being touched, with good stability. 2.Convenient angle adjustment: Open the angle adjustment switch, the touchscreen can be randomly adjusted in the range of 15-80. 3.Private mold, technical level conforms to international standard, designed with human body engineering and aesthetic principle. 4.The corer is made by the green fire-proof ABS materials,accordance with requirement of Rohs. 5.The machine is robust,durable and elegant with modern design.
---	--

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation force is less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	12-inch LCD panel
Resolution(pixel)SXGA:	800*600
Aspect Ratio:	4:3
Brightness:	300cd/m2
Contrast Ratio:	350: 1
Pixel Pitch:	0.297mm
View Angle:	160/160 (horizontal/vertical)
response time:	12ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0°C-+40°C, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10°C-50°C
SIZE	315mm*267mm*25mm
Agency Approval:	CCC,CE,CB

© 1997-2009, S.G. INTERNATIONAL GROUP H.K. LTD. All rights reserved.

Buji Town, Shenzhen 518123, China

Tel: +86-755-25387626 , 84701880 , Fax: +86-755-84701680

Sales email: sgled@vip.163.com

ISO 9001:2000



Cert. #801532



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display



SG1506 LCD Touch Monitor

- 1.Flat chassis design: using on the desk, the display does not swag when being touched, with good stability.
- 2.Convenient angle adjustment: Open the angle adjustment switch, the touchscreen can be randomly adjusted in the range of 15-80.
- 3.Private mold, technical level conforms to international standard, designed with human body engineering and aesthetic principle.
- 4.The corer is made by the green fire-proof ABS materials,accordance with requirement of Rohs.
- 5.The machine is robust,durable and elegant with modern design.

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation forceis less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	15-inch LCD panel
Resolution(pixel)SXGA:	1024*768
Brightness:	250cd/m2
Contrast Ratio:	500:1
Pixel Pitch:	0.297mm
View Angle:	140/120 (horizontal/vertical)
response time:	12ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0℃-+40℃, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10℃-50℃
size:	359mm×301mm×55mm
Agency Approval:	CCC,CE,CB

© 1997-2009, S.G. INTERNATIONAL GROUP H.K. LTD. All rights reserved.

Buji Town, Shenzhen 518123, China

Tel: +86-755-25387626 , 84701880 , Fax: +86-755-84701680

Sales email: sgled@vip.163.com

ISO 9001:2000



Cert. #801532



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display



SG1706 LCD Touch Monitor(wall-mounted)

1. Input mode VGA and DVI: there are five keys-presses at the left and right sides of display surface respectively, replacing the function of all the keys of keyboard and mouse and key combination.
2. There are three USB interfaces at the back of left side, convenient for connecting mobile hard disk and U disk.
3. Power supply: 12V direct current, very safe.
4. VGA output port: to connect camera and display for synchronous display.
5. Wall-mount design, matching clients' requirements, taking smaller place if compared with traditional requesting music counter

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation force is less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	17-inch LCD panel
Resolution(pixel)SXGA:	1280×1024
field frequency:	60-75hz
Active Area:	337.9*270.3
Brightness:	300cd/m2
Contrast Ratio:	800: 1
Pixel Pitch:	0.264mm
View Angle:	160/160 (horizontal/vertical)
response time:	5ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0°C-+40°C, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10°C-50°C
Physical size:	380mm*355mm*66mm
Package size:	500mm*450mm*245mm
Net weight:	7kg
Total weight:	8.5kg
Agency Approval:	CCC,CE,CB



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display



SG1706 LCD Touch Monitor

1. Input mode VGA and DVI: there are five keys-presses at the left and right sides of display surface respectively, replacing the function of all the keys of keyboard and mouse and key combination.
2. There is a brush pot at the back of right side, convenient for laying pen.
3. Power supply: 12V direct current, very safe.
4. VGA output port: to connect camera and display for synchronous display.
5. Flat chassis design: using on the desk, the display does not swag when being touched, with good stability.
6. Convenient angle adjustment: open the angle adjustment switch, the touch screen can be freely adjusted in the range of 15-80 .

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation force is less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	17-inch LCD panel
Resolution(pixel)SXGA:	1280×1024
field frequency:	60-75hz
Active Area:	337.9*270.3
Brightness:	300cd/m2
Contrast Ratio:	800: 1
Pixel Pitch:	0.264mm
View Angle:	160/160 (horizontal/vertical)
response time:	5ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0°C-+40°C, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10°C-50°C
Physical size:	380mm*355mm*66mm
Package size:	500mm*450mm*245mm
Net weight:	7kg
Total weight:	8.5kg
Agency Approval:	CCC,CE,CB

© 1997-2009, S.G. INTERNATIONAL GROUP H.K. LTD. All rights reserved.

Buji Town, Shenzhen 518123, China

Tel: +86-755-25387626 , 84701880 , Fax: +86-755-84701680

Sales email: sgled@vip.163.com

ISO 9001:2000



Cert. #801532



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display

	<p>SG1706B LCD Touch Monitor</p> <ol style="list-style-type: none"> 1. Private mold, technical level conforms to international standard, designed with human body engineering and aesthetic principle. 2.The design can meet the requirements of entertainment sites, there are cooling holes on shell, sufficient cooling and water-prevention. 3.the corer is made by the green fire-proof ABS materials,accordance with requirement of Rohs. 4.Various colours available for user's choosing, matching the sites decoration style. 5.Power supply: 12V direct current,very safe to use. 6.Display mode of horizontal screen and vertical screen. 7.Pillar is made of stainless steel, exquisite craftwork without manual trace. 8.The machine is robust,durable and elegant with modern design.
---	---

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation forceis less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	17-inch LCD panel
Resolution(pixel)SXGA:	1280×1024
field frequency:	60-75hz
Active Area:	337.9*270.3
Brightness:	300cd/m2
Contrast Ratio:	800: 1
Pixel Pitch:	0.264mm
View Angle:	160/160 (horizontal/vertical)
response time:	5ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0℃-+40℃, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10℃-50℃
Physical size:	380mm*355mm*66mm
Package size:	500mm*450mm*245mm
Net weight:	7kg
Total weight:	8.5kg
Agency Approval:	CCC,CE,CB



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display



SG1906 Wide screen LCD Touch Monitor

- 1.Flat chassis design: using on the desk, the display does not swag when being touched, with good stability.
- 2.Convenient angle adjustment: Open the angle adjustment switch, the touchscreen can be randomly adjusted in the range of 15-80.
- 3.Private mold, technical level conforms to international standard, designed with human body engineering and aesthetic principle.
- 4.The corer is made by the green fire-proof ABS materials,accordance with requirement of Rohs.
- 5.The machine is robust,durable and elegant with modern design.

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation force is less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	19-inch LCD panel
Resolution(pixel)SXGA:	1440×900
Aspect Ratio:	16:10
Active Area:	408.24*255.15
Brightness:	300cd/m2
Contrast Ratio:	800: 1
Pixel Pitch:	0.2835mm
View Angle:	160/160 (horizontal/vertical)
response time:	5ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0°C-+40°C, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10°C-50°C
Physical size:	500mm*345mm*70mm
Package size:	575mm*410mm*210mm
Net weight:	6.1kg
Total weight:	7.5kg
Agency Approval:	CCC,CE,CB



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display



SG1906 LCD Touch Monitor

- 1、 Non-substructure design: using on the desk, the display does not swag when being touched, with good stability.
- 2、 Convenient angle adjustment: Open the angle adjustment switch, the touchscreen can be randomly adjusted in the range of 15o-80o.

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation force is less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	19-inch LCD panel
Resolution(pixel)SXGA:	1280*1024
Aspect Ratio:	4:3
Active Area:	376.3*301.1
Brightness:	300cd/m2
Contrast Ratio:	1300: 1
Pixel Pitch:	0.294mm
View Angle:	178/178 (horizontal/vertical)
response time:	8ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0°C-+40°C, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10°C-50°C
Agency Approval:	CCC,CE,CB



S.G. INTERNATIONAL GROUP H.K. LIMITED

SHENZHEN SHUGUANG DIGITAL TECHNOLOGY CO., LTD.

Add: Gold industrial park, NanLing village, Buji Town, Shenzhen, China

Tel: (86)0755-25387626

84701880

84701680

Fax :(86)0755-84701680

[Http://www.sgcg-group.com](http://www.sgcg-group.com)

E-mail: sgled@vip.163.com

MSN: sgled@hotmail.com

Yahoo Messenger: sgled_usa@yahoo.com

➤ Touch liquid crystal display



SG2007 Wide screen LCD Touch Monitor

- 1.Flat chassis design: using on desk, the display does not swag when being touched, good stability.
- 2.Convenient angle adjustment: open the angle adjustment switch,the touch screen can be freely adjusted in the range of 15 degree-80 degree
- 3.Input: TV Input, AV Input, SVIDEO Input, VGA Input, PC Audio Input
- 4.Output: Headphone Audio, Audio Output.

Touch screen (selection):	surface sound wave screen, four-line and five-line resistance screen
Input equipmen(surface sound wave screen):	Choose the most advanced surface acoustic wave screen with the resolution of 4096*4096 and single-point touch for 50 million times, The response is more rapid and the life is the longest. The touch activation force is less than 3 ounces. The same surface hardness as glass, and Mohs'hardness test is 7-grade.
Display:	20.1-inch LCD panel
Resolution(pixel)SXGA:	1680*1050
Aspect Ratio:	16:10
Active Area:	433.4*270.9
Brightness:	300cd/m ²
Contrast Ratio:	800: 1
Pixel Pitch:	0.258mm
View Angle:	160/160 (horizontal/vertical)
response time:	5ms.
Power source and power:	100-240VAC,50-60hz,60w
Running environment:	WINDOWS95/98/2000/NT/XP/LINUX
Working environment:	temperature +0℃-+40℃, relative humidity 10%-90% (relative, non-compression)
Storage temperature:	-10℃-50℃
Physical size:	500mm*345mm*70mm
Package size:	575mm*410mm*210mm
Net weight:	6.1kg
Total weight:	7.5kg
Agency Approval:	CCC,CE,CB